

## Parameter list

| Serial NO. | Model                | Voltage | CCT **      | CRI   | lm/m *<br>lm/LED      | W/m<br>W/group         | LEDs/m<br>LEDs/group     | Min cutting<br>length | Max size           |
|------------|----------------------|---------|-------------|-------|-----------------------|------------------------|--------------------------|-----------------------|--------------------|
| 1          | CL-2835XW064HE24-W12 | DC 24 V | 2700-6500 K | Ra>80 | 900 LM/M<br>24-28 LM  | 6 W/M<br>0.75 W/Group  | 64 LED/M<br>8 PCS/Group  | 125mm                 | W:12mm*T:0.25mm*5m |
| 2          | CL-2835XW096HE24-W12 | DC 24 V | 2700-6500 K | Ra>80 | 1200 LM/M<br>24-28 LM | 8 W/M<br>0.667 W/Group | 96 LED/M<br>8 PCS/Group  | 83.3mm                | W:12mm*T:0.25mm*5m |
| 3          | CL-2835XW128HE24-W12 | DC 24 V | 2700-6500 K | Ra>80 | 1800 LM/M<br>24-28 LM | 12 W/M<br>0.75 W/Group | 128 LED/M<br>8 PCS/Group | 62.5mm                | W:12mm*T:0.25mm*5m |

\*Within 20% deviation for lumen and power in case of bulk shipment.

\*\*Most products are customizable, such as special CCT (2000K-2400K) or colour.

\*\*CCT tolerance range: (2700-3000K) ± 100K; (3500-4000K) ± 150K; (4500-6500K) ± 200K