

Parameter list

Serial NO.	Model	Voltage	CCT **	CRI	lm/m * lm/LED	W/m W/group	LEDs/m LEDs/group	Min cutting length	Max size
1	CL-3014XW060HY12-W05	DC 12 V	2700-6500 K	Ra>80	380 LM/M 10-12 LM	4.8 W/M 0.24W/Group	60 LED/M 3 PCS/Group	50mm	W:5mm*T:0.25mm*5m
2	CL-3014XW060HY24-W05	DC 24 V	2700-6500 K	Ra>80	380 LM/M 10-12 LM	4.8 W/M 0.48 W/Group	60 LED/M 6 PCS/Group	100mm	W:5mm*T:0.25mm*5m
3	CL-3014XW090HY12-W05	DC 12 V	2700-6500 K	Ra>80	570 LM/M 10-12 LM	7.2 W/M 0.24 W/Group	90 LED/M 3 PCS/Group	33.3mm	W:5mm*T:0.25mm*5m
4	CL-3014XW096HY24-W05	DC 24 V	2700-6500 K	Ra>80	600 LM/M 10-12 LM	7.6 W/M 0.475 W/Group	96 LED/M 6 PCS/Group	62.5mm	W:5mm*T:0.25mm*5m
5	CL-3014XW120HY12-W05	DC 12 V	2700-6500 K	Ra>80	760 LM/M 10-12 LM	9.6 W/M 0.24 W/Group	120 LED/M 3 PCS/Group	25mm	W:5mm*T:0.25mm*5m
6	CL-3014XW120HY24-W05	DC 24 V	2700-6500 K	Ra>80	760 LM/M 10-12 LM	9.6 W/M 0.48 W/Group	120 LED/M 6 PCS/Group	50mm	W:5mm*T:0.25mm*5m

*Within 20% deviation for lumen and power in case of bulk shipment.

**Most products are customizable, such as special CCT (2000K-2400K) or colour.

**CCT tolerance range: (2700-3000K) ± 100K; (3500-4000K) ± 150K; (4500-6500K) ± 200K