

Parameter list

Serial NO.	Model	Voltage	CCT **	CRI	lm/m * lm/LED	W/m W/group	LEDs/m LEDs/group	Min cutting length	Max size
1	CL-5050RGB030HY12-W10	DC 12 V	RGB RGB	/	/	7 W/M 0.7 W/Group	30 LED/M 3 PCS/Group	100mm	W:10mm*T:0.25mm*5m
2	CL-5050RGB060HY12-W10	DC 12 V	RGB	/	/	12 W/M 0.6 W/Group	60 LED/M 3 PCS/Group	50mm	W:10mm*T:0.25mm*5m
3	CL-5050RGB060HY24-W10	DC 24 V	RGB	/	/	12 W/M 1.2 W/Group	60 LED/M 6 PCS/Group	100mm	W:10mm*T:0.25mm*5m
4	CL-5050RGB120HY24-W20	DC 24 V	RGB	/	/	20 W/M 2 W/Group	120 LED/M 12 PCS/Group	100mm	W:20mm*T:0.25mm*5m
5	CL-5050RGB030HL12-W10 (pixel led strip)	DC 12 V	RGB	/	/	14 W/M 1.4 W/Group	60 LED/M 6 PCS/Group	100mm	W:10mm*T:0.25mm*5m
6	CL-5050RGB060HL24-W10 (pixel led strip)	DC 24 V	RGB	/	/	14 W/M 1.4 W/Group	60 LED/M 6 PCS/Group	100mm	W:10mm*T:0.25mm*5m
7	CL-5050RGB30HL5-W10 (pixel led strip)	DC 5 V	RGB	/	/	5 W/M 0.17 W/Group	30 LED/M 1 PCS/Group	100mm	W:10mm*T:0.25mm*5m

*Within 20% deviation for lumen and power in case of bulk shipment.

**Most products are customizable, such as special CCT (2000K-2400K) or colour.

**CCT tolerance range: (2700-3000K) ± 100K; (3500-4000K) ± 150K; (4500-6500K) ± 200K