

Parameter list

Serial NO.	Model	Voltage	CCT **	CRI	lm/m * lm/LED	W/m W/group	LEDs/m LEDs/group	Min cutting length	Max size
1	CL-2110XW120HY12-W05	DC 12 V	2700-6500 K	Ra>90	84LM/W 9-10LM	6.2W/m	120PCS/M 3PCS/Group	25mm	W:5mm*T:0.25mm*5m
2	CL-2110XW120HY24-W05	DC 24 V	2700-6500 K	Ra>90	84LM/W 9-10LM	6.2W/m	120PCS/M 6PCS/Group	50mm	W:5mm*T:0.25mm*5m
3	CL-2110XW168HY12-W05	DC 12 V	2700-6500 K	Ra>90	86LM/W 9-10LM	7.5W/m	168PCS/M 3PCS/Group	17.6mm	W:5mm*T:0.25mm*5m
4	CL-2110XW168HY24-W05	DC 24 V	2700-6500 K	Ra>90	86LM/W 9-10LM	7.5W/m	168PCS/M 6PCS/Group	35.2mm	W:5mm*T:0.25mm*5m
5	CL-2110XW192HY12-W05	DC 12 V	2700-6500 K	Ra>90	89LM/W 9-10LM	9.6W/m	192PCS/M 3PCS/Group	15.6mm	W:5mm*T:0.35mm*5m
6	CL-2110XW192HY24-W05	DC 24 V	2700-6500 K	Ra>90	89LM/W 9-10LM	9.6W/m	192PCS/M 6PCS/Group	31.2mm	W:5mm*T:0.35mm*5m
7	CL-2110XW240HY12-W05	DC 12 V	2700-6500 K	Ra>90	91LM/W 9-10LM	12.5W/m	240PCS/M 3PCS/Group	12.5mm	W:5mm*T:0.35mm*5m
8	CL-2110XW240HY24-W05	DC 24 V	2700-6500 K	Ra>90	91LM/W 9-10LM	12.5W/m	240PCS/M 6PCS/Group	50mm	W:5mm*T:0.35mm*5m

*Within 20% deviation for lumen and power in case of bulk shipment.

**Most products are customizable, such as special CCT (2000K-2400K) or colour.

**CCT tolerance range: (2700-3000K) ± 100K; (3500-4000K) ± 150K; (4500-6500K) ± 200K